



# **Scapa 3159**

# Waterproof Cloth Tape

# **DESCRIPTION**

Scapa 3159 is an economy grade, polyethylene laminated cloth tape, coated with a pressure sensitive natural rubber resin adhesive. Scapa 3159 is available in silver, black and white only.

#### **APPLICATIONS**

- Designed as a general purpose cloth tape for a full range of industrial and construction applications:
- Sealing
- Bundling
- Short term masking
- Protection

#### **PRODUCT BENEFITS**

- Service temperature -10 to +75°C
- Good all purpose product
- Good low temperature performance
- Flexible and conformable
- · Good adhesion and strength
- Good water resistance

# **TECHNICAL PROPERTIES**

Technical Property	Nominal Value	Unit	Test Method
Thickness (mm)	0.14	-	AFERA 5006*
Tensile Strength	35	N/cm	IEC 454-2
Adhesion to Steel	4	N/cm	IEC 454-2
Adhesion to Backing	2.5	N/cm	IEC 454-2

Version: 1 Date: 12/11/2015 Page: 1 of 2

www.scapa.com

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

## STANDARD PRESENTATIONS

- Roll Width: 48mm and 72mm only
- Roll Length: 50m
- Packaging: Shrink wrapped in packs of 4 with 6 packs to a carton (48mm), Shrink wrapped in packs of 4 with 4 packs to a carton (72mm)
- Core: Plain Cardboard
- Colours: Black, white and silver

## **RECOMMENDATIONS**

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Shelf life will vary with conditions of use and is affected by climate environment, but should not be less than two years from date of manufacture, if stored in a moderate climate and good conditions.

Version: 1 Date: 12/11/2015 Page: 2 of 2

www.scapa.com