



Scapa 3362

Unbleached Cotton Cloth Tape

DESCRIPTION

Scapa 3362 is a general purpose unbleached cotton cloth tape with pressure sensitive adhesive. Scapa 3362 is available in a natural colour shade.

APPLICATIONS

- Also suitable for use for heavy duty general purpose sealing, packaging, bundling and binding applications
- Protection of polished surfaces and machined parts against corrosion
- Masking off of cats eye's, grids, manhole covers etc, during road resurfacing work

PRODUCT BENEFITS

- Service Temperature of -10 to +60 °C
- An economic cloth tape for general purpose applications
- Can be written on
- · High initial tack and adhesion
- Easy tear by hand
- Flexible and highly conformable
- Abrasion resistant
- · Corrosion resistant

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Tensile Strength	70	N/cm	IEC 454-2
Adhesion to Steel	3	N/cm	IEC 454-2
Thickness	0.29	mm	AFERA 5006*

Version: 1 Date: 12/11/2015 Page: 1 of 2

www.scapa.com

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

STANDARD PRESENTATIONS

• Packaging: Scapa branded, bulk packed using interleaving sheets between layers.

• Core: Cardboard

• Roll Width: 19mm, 25mm, 38mm, 50mm, 75mm, 100mm

• Roll Length: 25m, 50m

Note:

Note: Information on stock items, non-standard sizes, and lead times is available on request.

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants Shelf life will vary with conditions of use and is affected by climatic environment, but it is recommended that the product should be used within 6 months of date of manufacture, if stored in a moderate climate and good conditions.

Version: 1 Date: 12/11/2015 Page: 2 of 2

www.scapa.com