

tesaflex® 4252

PVC Electrical Insulation Tape

tesa® 4252 is an economic grade of plasticised PVC tape with good flexibility and electrical properties.

Having a modified rubber resin adhesive coating, tesa® 4252 provides good adhesion and ageing resistance in most applications.

Main Application

tesa® 4252 is suitable for most electrical insulation applications such as splicing and protection.

The assorted colour range of tesa® 4252 makes it useful in decorative and colour coding applications as well.

Technical Data

▪ Backing material	soft PVC	▪ Adhesion to steel	2.8 N/cm
▪ Total thickness	120 µm	▪ Elongation at break	180 %
▪ Type of adhesive	natural rubber	▪ Tensile strength	20 N/cm

Properties

▪ Certified according to	none
--------------------------	------

For latest information on this product please visit <http://l.tesa.com/?ip=04252>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.