

tesa® 4328

High quality general purpose paper masking tape available in colours

tesa® 4328 is a finely crêped paper masking tape with a natural rubber adhesive.

tesa® 4328 can be used on various surfaces including painted metal, rubber, glass and chromed parts.

Main Application

The product is recommended for bundling, bag sealing, marking and general purpose masking applications.

Technical Data

▪ Backing material	slightly-creped paper	▪ Elongation at break	12 %
▪ Total thickness	175 µm	▪ Tensile strength	42 N/cm
▪ Type of adhesive	natural rubber	▪ Temperature resistance	140 °C
▪ Adhesion to steel	4.8 N/cm		

Properties

▪ Hand tearability	●●●●	▪ Sharp colour edge	●●●
▪ Easy to remove	yes	▪ Conformability	●●●
▪ Paint anchorage	●●●●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

tesa® 4328 is suitable for masking during paint spray painting with oven drying (up to 80 °C).

After the oven drying process tesa® 4328 can be easily removed without tearing and without leaving any residues.

The product is easily tearable by hand.

For latest information on this product please visit <http://l.tesa.com/?ip=04328>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.