

# PRODUCT DATA SHEET



## HIGH GRADE GAFFER - RS190

### TECHNICAL DATA

<b>Tape Grade</b>	Cloth tape 70 Mesh
<b>Base carrier</b>	65% polyester, 35% cotton, Woven cloth
<b>Adhesive</b>	Natural rubber base
<b>Total thickness (micron)</b>	300
<b>Peel adhesion (gf/25mm/180°)</b>	1250
<b>Tensile strength (kgf/25mm)</b>	13.5
<b>Elongation (%)</b>	10.5
<b>Ball tack (Ball No.)</b>	27
<b>Holding power (mm/Hr)</b>	0.5kg loading on SUS plate, 25mm×25mm
<b>Un-winding force (gf/25mm)</b>	650
<b>Heat resistance (°C/min)</b>	85/180
<b>Weather resistance (Hr)</b>	8
<b>Average weight</b>	450g 50mmx25m
<b>Length</b>	25m↑
<b>Delamination</b>	No

Above test were performed on the condition of 23±2°C and humidity of 65±5% (JIS Z 0237, 1254). All above data can be changed according to testing circumstances.

This is to certify that our product is identified with the specification as indicated above and declare that JIS Z 0237, 1254 is fundamentally same with American Spec SAT-DO 5486.

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.