

# PRODUCT DATA SHEET



## **DROP DOWN FILM GAFFER – RS251**

### **FEATURES AND BENEFITS**

Excellent adhesion properties at low & high temperatures.

Good performance on rough surface.

Excellent tearing & unwinding.

Leaves no residue.

Good in external/internal uses and good UV resistance.

<b>Item</b>	Paintable Masking Film
<b>Usage</b>	Automotive Refinishing Works
<b>Material</b>	100% Virgin of High Density Polyethylene
<b>Colour</b>	Transparent(HDPE Natural Color)
<b>Thickness</b>	0.010mm ± 3%
<b>Width</b>	4.0m
<b>Heat Resistance</b>	10°C - Max 140°C(Working range in Spray booth)
<b>Corona Treatment</b>	44 Dyne by treator

### **SPECIFICATION**

Sticks immediately to the surface of the car when places on it.

Very flexible, suits the shape of the car and does not tear.

Transparent, can be cut in the exact size.

The car can still be moved when it is already masked.

It does not give off fluff and dust when cutting.

The paint sticks to the film and does not peel off when it is dry.

Continued...

## **SPECIFICATION** continued...

No more dust in the paintwork.

Closed surface structure. The paint cannot get through.

Resistant to spray booth temperatures and infrared drying.

Absolutely waterproof, even when used with waterbased paint.

Resistant to compressed air, can be blown dry.

Can be compressed to minimum dimensions. Less waste.

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.