

PRODUCT DATA SHEET



AQUA ANTI-SLIP – RS880

DESCRIPTION

The aqua-safe & non abrasive anti slip tape range has a unique non slip coating to ensure an effective non slip flooring, yet has a smoother surface for walking bare foot on and no abrasion to prevent damage to skin, material or wet suits.

SUBJECT	RESULT	TEST METHOD
Back Carrier	0.4mm PVC	Caliper method
Total applied thickness	0.99mm	Caliper method
Total thickness	1.2mm	Caliper method
Type of adhesive	Solvent acrylic	N/A
Mineral type	S2	N/A
Adhesion to steel (g/25.4mm ²)	1500↑	PSTC-4
Tensile strength (Kg/25.4mm ²)	5.0↑	PSTC-31
Elongation at break	5%↑	PSTC-31
Temperature range	-30°C to +70°C	See notes below
Maximum size of production roll	1060mm x 100m	N/A
Resistance to water (months)	10	PSTC-35
Resistance to chemicals (months)	8	PSTC-35
Resistance to motor oil	Excellent	PSTC-35
Life (months)	12 to 24	PSTC-9

Continued...

KEY BENEFITS

- Unique non-slip coating, possesses a high coefficient of friction
- No harsh grit granules
- Permanent adhesive coating
- Available in five popular colours – black, white, beige, grey and clear, others available on request
- Any width/shape available
- Easy, instant application
- A great anti slip marine tape
- Creates an excellent non slip flooring, an excellent safety tape

We have tested all the range for levels of grip, the tests include Pendulum, ASTM and DIN

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.

Reliable Source Ltd – 1 High Street – Chislehurst – Kent – BR7 5AB

T: 020 8295 5440 F: 020 8295 5441

E: sales@reliablesource.co.uk W: www.reliablesource.co.uk