

PRODUCT DATA SHEET



PRINTABLE ECO PAPER TAPES – RS214

DESCRIPTION

A Kraft paper carton sealing tape suitable for manual and automated application. Designed to offer a positive, attractive seal and excellent adhesion to minimize carton-sealing failures and prevent pilferage.

TECHNICAL DATA

Paper Thickness	90 Micron
Total Thickness	110 Micron
Peel Adhesion	8,5 N/cm
Tensile Strength	45 N/cm
Holding Power to Kraft @ 50°C in oven	100 hours
Application Temperature	6°C to 45°C
Service Temperature	-10°C to 60°C

Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

ADVANTAGES AND BENEFITS

- Excellent adhesion even on recycled cartons
- Good tack
- Printable
- Hand tearable

CONSTRUCTION

Backing: Kraft paper

Adhesive: Recycled synthetic rubber and hydrocarbon resins.

Colours: Brown and white.

Continued...

STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.